

RendX Primer

Product data sheet

Product description

RendX is a Primer applied to the substrate (brick or stone) by brush or coarse spray before applying render-based plasters. RendX Primer is a water-based solution with a surfactant and offers the following benefits:

Reduces the risks of salt contamination of the render-base plaster when plastering walls affected by rising damp or penetrating damp.

Directions for use

Wet down the substrate with clean water before applying RendX Primer.

Apply RendX Primer to the substrate by brush or coarse sprayer up to 12 hours before applying render. Carry out a second application of RendX Primer approximately 30 minutes before applying render.

RendX Primer is a ready-to-use formulation – do not dilute.

Use RendX Admix in the render coats.

Coverage and pack size

RendX Primer is supplied in a ready-to-use 5 litre container (typical coverage: 15m²).

Health and Safety information

Read product label and refer to the Manufacturer's Safety Data Sheet (MSDS) before use (available online at www.dampexpert.com).

Wear suitable protective clothing when using this product including waterproof gloves, eye and face protection. Do not breathe fumes. In case of contact with eyes, rinse with water. Medical attention should be sought in the case of accidents or if you feel unwell following use of this product.

Additional information

The above information is provided in good faith based on our knowledge and experience of the materials used. However, since application of RendX Primer is outside of the control of Damp Expert Ltd., we cannot accept any responsibility for loss or damage resulting from use of the product outside the scope of the intended use and precautions set out on the product label, data sheet or Manufacturer's Safety Data Sheet.

Manufacturer information

Damp Expert Ltd.,
Birdsgrove,
SK17 0DH.
Telephone 0800 169 1106