

ulthrotherm[®]

Tile Adhesive



ULTROTHERM SPRAY ADHESIVE

Unchlorinated, low odour adhesive used for the bonding of Ultratherm tiles to various wall surfaces including plaster, plasterboard and wood panels

COVERAGE

Each can of Ultratherm spray adhesive is sufficient to bond 5 Ultratherm tiles (2.5 m²). 2 cans of spray adhesive are required for each pack of 10 Ultratherm tiles.

APPLICATION

1. Shake can well before use.
2. Spray from a distance of 200m – 300mm onto the surface receiving the Ultratherm tile and onto the reverse side of the Ultratherm tile.
3. Allow the adhesive to become tacky, typically 60-90 seconds dependent on ambient room temperature.
4. Firmly press the Ultratherm tile onto the adhesive ensuring the join to adjacent tiles is the first point of contact. Avoid pulling the tile across the adhesive.
5. Following use, invert the spray can and spray once to prevent spray head clogging or blocking.
6. Excessive adhesive can be removed by wiping with white spirit or similar solvent.

USE IN A WELL VENTILATED AREA.

DANGER



UK CA

ULTROTHERM SPRAY ADHESIVE: Contains Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane, ACETONE

UN1950

Extremely flammable aerosol.
Pressurised container: may burst if heated.
Causes skin irritation.
May cause drowsiness or dizziness.
Causes serious eye irritation.
Harmful to aquatic life with long lasting effects.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wear protective gloves/protective clothing/ eye protection/ face protection.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with national regulations.
Repeated exposure may cause skin dryness or cracking.

ulthrotherm.com
0800 169 1106

CONTENTS
500ml e **650** 3